

MBRP

MBRP Muffler Installation Instructions

1190215 – 119T110

2009-2015

Skidoo REV XR MXZ/

GSX/Renegade 1200 4-TEC

Note: Local regulations may limit or prohibit modification to your snowmobile's emissions system and/or the sound levels that it generates. It is your responsibility to be aware of restrictions that may apply to your intended use of this product.

1. Remove the springs fastening the stock muffler to frame and exhaust pipe. (Set springs safely aside so they can be reused)
2. Remove the stock muffler.
3. Install the MBRP muffler, placing its outlet through the stock exit in the belly pan.
4. Align the MBRP muffler inlet with the remaining stock exhaust. Mark the hole of the base plate of the MBRP muffler on the belly pan.
5. Remove the MBRP muffler and drill a 5/16" hole through belly pan on the marked location.
6. Re-install MBRP muffler using the stock spring to fasten the canister and use the provided hardware to bolt the base plate of the muffler to the belly pan through the previously drilled hole.

NOTE: To avoid exhaust leaks use high heat silicone to seal all connections between expansion chambers and muffler. Monitor for leaks during the first 200 miles after your installation and re-apply silicone where necessary. We suggest having your local snowmobile mechanic or performance shop install this product.

CAUTION: **DO NOT** touch muffler while snowmobile is running or shortly after it has run, as it may result in personal injury.

MBRP Ltd. warranty applies for a two (2) year period from the date of purchase to defects in product material and workmanship and is to the original purchaser on record and for the original vehicle for which it was designed and installed. This warranty is limited, at MBRP Ltd. sole determination, to the repair or replacement of defective product only and does not include the cost of removal or re-installation, damage by accident, abuse, misuse or misapplication or any consequential damages however they may arise. Determination of warranty coverage shall be at the discretion of an authorized MBRP Ltd. quality engineer.

